



5-140KVA

Engine Characteristics: Typical Engine Features

- Lister Petter 2/3/4/6 cylinder
- Direct injection.
- Turbocharged if needed (LPWT).
- Water cooled.
- Diesel fuelled.
- Anti-clockwise rotation, looking on the flywheel end.
- Fuel filter.
- Heavy duty air cleaner.

Extra Design Features:

Remote Monitoring with WS200 Netbiter on request
 Bulk Storage tanks and Fuel make up systems
 Canopy Sets 75Db@3m
 ATS Panel

Standard Equipment:

Engine
 Alternator ENGGA
 Radiator
 AV mounts
 12V Battery
 Key Start DSE511 Control Panel
 Silencer
 Skid with Base Tank
 MCCB

The complete ENGINE range

New ALPHA Series: LPWS2, LPWS3, LPWS4, LPWST4

The NEW ALPHA (LPWS) is the emission compliant version of the ALPHA engine. Closely based on the LPW, it has the advantages of ALPHA technology and is designed for compliance with emission regulations in Europe and the USA

DELTA Series: DWS The 4-cylinder DELTA engine is the bigger brother of the ALPHA and is available in both variable and fixed speed in both variable and fixed speed builds.

GAMMA Series: GW4, GWT4, GWT6-1A, GWT6-2A, GWTA6 heavy-duty G-Build engine in the middle power band of 38 kVA to 138 kVA. GAMMA is offered in both a 4-cylinder and a 6-cylinder version, either naturally aspirated or turbocharged

| Engine | SIGMA 30 | GW4 | GWT4 | GWT4 | GWT61A | GWT6A | GWT6A | GWT6A |
|--------|----------|-----|------|------|----------|-------|-------|-------|
| KVA | 30 | 40 | 50 | 62.5 | 75 /82.5 | 112.5 | 125 | 138 |

MALCO ENGINEERING SDN BHD

Reg Office Suite 1, 1st Floor, "WISMA LEOPAD"5, Jalan Tun Sambanthan, 50470 Kuala Lumpur, Malaysia.

Sales and Factory 6, Jalan Tiara 2, Taan Perindustrian SIME UEP 47600 Subang Jaya, Selangor

Tel +60173784237 email: info@malcoengineering.com web www.malcoengineering.com